


COMBINED SENSOR



for three parameters: Temperature - Humidity - Pressure



The sensor (8095-N)...

is a combined measuring instrument for measuring relative humidity, air temperature and air pressure.

The sensor is characterised by a power-saving electronic. The membrane filter reliably protects the capacitive measuring element from air pollutants.

- ▶ combined measuring instrument for high-quality use
- ▶ capacitive humidity measuring element
- ▶ low maintenance
- ▶ special resistance to air pollutants
- ▶ signal output humidity: RS 422/ Talker · NMEA
- ▶ for use in all climatic zones

high-quality use in meteorology and on ships

Professional Line	(8095-N) THP Sensor	Id-No. 00.08095.001 000
Temperature		
Measuring range:	-40...+70 °C	
Resolution:	0.1 °C	
Accuracy:	± 0.3 °C at (v > 2 m/s) • ± 0.4 °C (10 ... 40 °C) • ± 0.8 °C (-10 ... 70 °C)	
Relative humidity		
Measuring range:	0...100 % r. h.	
Resolution:	0.1 % r. h.	
Accuracy:	± 3 % (10...90 %) r. h. ¹⁾ • ± 4 % (0...100 %) r. h. Reaction time rel. humidity (at v = 1.5 m/s): 30 s ²⁾	
Barometric pressure		
Measuring range:	500...1100 hPa	
Resolution:	0.1 hPa	
Accuracy:	± 2 hPa (-30...+70 °C) • ± 1 hPa (-10...+60 °C)	
Supply voltage:	4.8...33 V DC	
Current consumption ³⁾ :	4 mA at 24 V DC • 6 mA at 12 V DC • 11 mA at 4.8 V DC M12 Plug connector (4-pole) • protection class IP65/IP68/IP69K (with plug inserted)	
Housing:	Aluminium especially-coated • IP 65 (housing) • IP 65 (filter)	
Weight/ Dimensions:	approx. 80 g • H 140 mm x Ø 20 mm	
Interface:	Serial RS 422/ Talker • Baudrate 4800 • 1 Hz • 8 N 1	
Protocols:	NMEA 0183 • WIMHU • WIMMB • WIMTA	

¹⁾ Temperature influence of the shelter: < ± 0.1 % r.h. at +10...+40 °C

²⁾ with filter membrane ³⁾ at NMEA without terminating resistor