

HUMIDITY-TEMPERATURE SENSOR

Shock and vibration-tested...

precision instrument for measuring relative humidity and air temperature. The compact sensor is characterised by a power-saving electronic and high measuring accuracy. A membrane filter reliably protects the high-quality capacitive measuring element from air pollutants.


- shock- and vibration-tested in accordance with BV0230/ 0430 and BV0440/ 0240
- EMC-proved in accordance with VG 95373
- sensor is supplied with Calibration Certificate
- high measuring accuracy
- special resistance to air pollutants
- high long-term stability

ships • high-quality use in meteorology and industry • automatic weather stations in all climatic zones

Sensor 8096-Z



Sensor shelter (accessory)



Professional Line	(8096-Z)	Humidity-Temperature Sensor	Id-No. 00.08096.330402
Measuring elements:		Humidity: capacitive Temperature: Pt100 1/3 DIN (DIN EN 60571) · IEC 751 Class B ($\pm 0.1 \text{ }^\circ\text{C}$)	
Range of application:		0...100 % r. h. • $-40...+70 \text{ }^\circ\text{C}$	
Measuring range:		0...100 % r. h. • $-40...+70 \text{ }^\circ\text{C}$	
Accuracy:		Humidity: $\pm 2 \text{ } \%$ r. h. at: 5...95 % r. h. • $+10...+40 \text{ }^\circ\text{C}$ (at $\geq 0.5 \text{ m/s}$) Plus: $< 0.1 \text{ } \%$ r. h./ $^\circ\text{C}$ at: $< +10 \text{ }^\circ\text{C}$ • $> +40 \text{ }^\circ\text{C}$ Temperature: $\pm 0.1 \text{ }^\circ\text{C}$, 1/3 DIN IEC 751 Class B	
Response time:		Humidity: $< 20 \text{ s}$ (without wind and without filter, otherwise at 1.5 m/s : 1.5 min)	
Minimum air velocity:		$\geq 0.5 \text{ m/s}$	
Output signal:		Humidity: $0...1 \text{ VDC} = 0...100 \text{ } \%$ r. h. • min. load resistance $\geq 2 \text{ k}\Omega$ Temperature: Pt100 (4-wire circuit)	
Supply voltage:		6...30 VDC	
Current consumption:		$< 1 \text{ mA}$	
Sensor protection:		membrane filter for outdoor use	
Cable:		3.3 m · fixed cable	
Housing/ Weight:		stainless steel · IP 65 · protection class of filter IP 40 • approx. 0.3 kg	
EMC:		DIN EN 60945 - Chapter 9, 10 + VG 95 373	
Shock/ Vibration:		BV0230/ 0430 • BV0440/ 0240	
<u>Accessory:</u>		Sensor shelter for protection of the sensor against radiation influences	
00.08141.620 000			