



Saving Time • Saving Money • Conserving Resources

ISO 9001:2008
CERTIFIED COMPANY

Low Flow Meters



PLASTIC MECHANICAL




SPX/SPT

Flow Rates from 0.07 GPM to 40 GPM
Pulse Output (Optional 4-20mA)
Jewel Bearings

For metering low-flow chemicals and fertilizers, these mechanical meters are offered with a variety of O-ring and shaft materials to fit your application.

STAINLESS MECHANICAL



SES

Flow Rates from 0.1 GPM to 25 GPM
Pulse Output (Optional 4-20mA)
Jewel Bearings

For low-flow chemical metering, the SES has a high tolerance for problem fluids. Various O-ring and shaft materials are available.

INSERTION PADDLEWHEEL



LOW FLOW MAGMETER



PE202

Flow Rates from .03 GPM to 20 GPM
Pulse and 4-20mA Output
No Moving Part

The PE102 is designed for low-flow chemical and fertilizer injection or difficult applications with pulsating metering pumps.

PLATED BRASS MECHANICAL



SEB

Flow Rates from 0.2 GPM to 18 GPM
Pulse Output (Optional 4-20mA)
Jewel Bearings

The SEB is a plated brass low flow meter suited for clean water. It is available in 1/2" and 3/4" thread, with union-type meter couplings for easy installation and service.

IP800 Series

0.28 - 28 GPM
1/2" - 8" Pipe Sizes
Jewel Bearings

PVC, Polypro, Brass or Stainless Steel

Bodies are machined from a solid rod for maximum precision. Jewel bearings and nickel-bound tungsten carbide shafts are used for low flow performance.