



Saving Time • Saving Money • Conserving Resources

ISO 9001:2008
CERTIFIED COMPANY

Dirty, Grey & Waste Water Applications



FLANGED FULL-BORE



iMAG Series

- 3" - 12" Sizes
- Programmable Display
- 2:1 Straight Pipe
- Pulse or 4-20mA Output
- Burial & Submersion Optional

Unobstructed flow and electrodes designed to discourage fouling allow these meters to be used in dirty and waste water applications.



FLANGED FULL-BORE




WMX Series

- 3" - 12" Sizes
- External or Battery Powered
- 2:1 Straight Pipe
- Pulse or 4-20mA Output
- Burial & Submersion Optional

Unobstructed flow and minimal straight pipe requirements allow these meters to be used where there is little installation space and extremely poor water quality.

ADJUSTABLE DEPTH INSERTION



EX100/200 Series

- 3" - 48" Adjustable depth
- Stainless Steel or Brass
- Externally Powered
- Hot Tap Available

With no moving parts, these meters are low maintenance and fit a variety of pipe sizes, types and poor water conditions.

PLASTIC MAGMETER



WMP Series

- 1" - 3" Sizes
- External or Battery Powered
- 2:1 Straight Pipe
- Polypro Body
- Pulse Output (101 only)

The WMP's polypropylene flow tube offers corrosion resistance and unobstructed flow. It's light weight and easy to install or remove.

FIXED DEPTH INSERTION



EX800 Series

- 1" - 12" Fixed Depth
- Externally Powered
- Stainless Steel, PVC or Brass

A choice of materials allows the meter to adapt to a range of temperature, pressure, and corrosive environments.